

VIVA 74

Product line: Silverline

We are energy - saving, modest and ecological. We do really good in calm, safe estates. Thanks to the wide color range, we fit every building.

PRODUCT INFORMATION

PRODUCT DESCRIPTION

Viva 74 is:

- a profile with a building depth of 74 mm;
- A 5-chamber system, which provides a very good thermal insulation
- Reinforcements made of steel in the frame and wing, which provide high static parameters;
- An easy care thanks to the big and smooth notch surface;
- Using of recycled materials in the pvc production process, which contributes to the environment protection thanks to the optimalization of consuming resources
- A layout of two thrust gaskets, which provide a very good tightness and acoustic and thermal insulation
- A classical profile line, thanks to which windows fit every elevation type
- A low total height of the frame and wing (116mm), which provides a better interior elucidation
- The possibility of using glazing packets from 22 to 46 mm
- Designed as an object window which makes it possible to connect economic, thermal and ecological parameters ideally



Insulation
1,2W/m²*K



Soundproof
max 42dB



Security
max RC2



COLOR



Oregon IV



Gold oak 2178.001



Brown 8875.05




Nut 2178.007



Bog oak 2052.089



Bog oak



Rustic oak




Creamy white




Dark-gray



Mahogany 2065.021



Black-brown 8518.05



Burgundy 3005.05



Red-Brown 3081.05



Dark-green 6125.05



Moss-green 6005.05




Navy Blue 5150.05




Brilliant blue 5007.05



Kwarcowo-szary 7039.05



Dark-gray 7016.05




Basalt-gray 7012.05




Silver-gray smooth
7155.05-083



Agate-gray 7038.05



Light gray 7251.05




Macore 3162.002




Light oak 3118.076



Mugo pine 3069.041



Winchester 49240



Siena noce 49237



Acrylcolor DB703



Acrylcolor White
aluminium



Acrylcolor Silver



Acrylcolor Slate gray




Acrycolor Gray



Acrycolor brown sepia



Acrycolor Black-brown



9016 RAL

SPECIFICATIONS

BUILDING DEPTH

74 mm

THERMAL INSULATION

In connection with a standard glazing 4/16/4 $U_g = 1,1 \text{ W/m}^2\text{K}$ the $U_w = 1,2 \text{ W/m}^2\text{K}$. With the 4/14/4/14/4 $U_g = 0,6 \text{ W/m}^2\text{K}$ the U_w factor $0,89 \text{ W/m}^2\text{K}$

GASKETS

Modern EPDM gaskets with a shape memory, available in: black, gray or optionally caramel

NUMBER OF CHAMBERS

5

FITTING

The modern Maco Multi fitting, equipped with anti-brake in plugs i.S (intelligent Safety)

GLASS

The Viva 74 windows are in the standard equipped with a compound glazing 4/16/4 $U_g 1,1 \text{ W/m}^2\text{K}$. It is possible to make windows with glazing 4/12/4/12/4 or 4/14/4/14/4 with factors $U_g = 0,7$ or $U_g = 0,6 \text{ Wm}^2/\text{K}$

PICTURES



