

DECLARATION OF PERFORMANCE

No V/S82/D/01/07/2018

1. Unique identification code of the product-type **CLIMA STAR 82 - external pedestrian doorset - Veka Softline 82**
2. Intended use/es: External pedestrian doorset without resistance to fire and/or smoke leakage characteristics, intended to be used in domestic and commercial locations
3. Manufacturer: Filplast Sp. z o.o.
ul. 3 Maja 33
PL-48-250 Głogówek
Poland
4. Authorised representative: -
5. System/s of AVCP: 3
- 6a. Harmonised standard: EN 14351-1:2006+A2:2016
- Notified body/ies: No 0757, IFT Rosenheim GmbH.

7. Declared performance/s:*

Essential Characteristics	Performance	Harmonised standard
7.1. Watertightness	4A	EN 14351-1:2006+A2:2016
7.2. Dangerous substances	npd	
7.3. Resistance to wind load	C2	
7.4. Load-bearing capacity of safety devices	threshold value reached: ≥ 350 N	
7.5. Thermal Transmittance	$U_d \leq 1,5$ W/(m ² .K)	
7.6. Radiation properties	Solar factor: $g \leq 0,65$	
	Light transmittance: $\leq 0,82$	
7.7. Air permeability	3	
7.8. Height and width	npd	

The performance of the product(s) identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Jacek Sikorski
Dyrektor ds. Technicznych
Głogówek, dnia 20.07.2018



No V/S82/D/01/07/2018

Manufacturer:
Filplast Sp z o.o., ul. 3 Maja 33,
PL-48-250 Głogówek, Poland
13



PN-EN 14351-1:2006+A2:2016

External pedestrian doorset without resistance to fire and/or smoke leakage characteristics, intended to be used in domestic and commercial locations

Notified body/ies: No 0757

CLIMA STAR 82 - external pedestrian doorset - Veka Softline 82

Declared performance/s:

Essential Characteristics	Performance	Harmonised standard
1. Watertightness	4A	EN 14351-1:2006+A2:2016
2. Resistance to wind load	C2	
3. Load-bearing capacity of safety devices	threshold value reached: ≥ 350 N	
4. Thermal Transmittance	$U_d \leq 1,5$ W/(m ² .K)	
5. Radiation properties	Solar factor: $g \leq 0,65$	
	Light transmittance: $\leq 0,82$	
6. Air permability	3	