DECLARATION OF PERFORMANCE

No V/C/S82/01/07/2013

1. Unique identification code of the product-type CLIMA STAR 82 - windows - Veka Softline 82

2. Intended use/es:

Single and multi-leaf windows and balcony doors without resistance to fire and/or smoke leakage

characteristics, intended to be used in domestic and commercial locations

3. Manufacturer: Filplast Sp. z o.o.

ul. 3 Maja 33

PL-48-250 Głogówek

Poland

4. Authorised representative:

5. System/s of AVCP: 3

6a. Harmonised standard: EN 14351-1:2006+A2:2016

Notified body/ies: No 0757, IFT Rosenheim Gmbh.

7. Declared performance/s:*

Essential Charakteristics	Performance	Harmonised standard
7.1. Watertightness	7A	EN 14351-1:2006+A2:2016
7.2. Dangerous substances	npd	
7.3. Resistance to wind load	C3	
7.4. Load-bearing capacity of safety devices	threshold value reached: ≥350 N	
7.5. Acoustic performance	Rw ≥ 33 dB (-1; -5)	
7.6. Thermal Transmitance	Uw ≤ 1,3 W/(m².K)	
7.7. Radiation properties	Solar factor: g ≤ 0,65	
	Light transmittance: ≤ 0,82	
7.8. Air permability	3	

The performance of the product(s) identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Jacek Sikorski Dyrektor ds Technicznych Głogówek, doją 20.07.2018



No V/C/S82/01/07/2013

Manufacturer: Filplast Sp z o.o., ul. 3 Maja 33, PL-48-250 Głogówek, Poland 13



PN-EN 14351-1:2006+A2:2016

Single and multi-leaf windows and balcony doors without resistance to fire and/or smoke leakage characteristics, intended to be used in domestic and commercial locations

Notified body/ies: No 0757

CLIMA STAR 82 - windows - Veka Softline 82

Declared performance/s:

Essential Charakteristics	Performance	Harmonised standard
1. Watertightness	7A	EN 14351-1:2006+A2:2016
2. Resistance to wind load	C3	
3. Load-bearing capacity of safety devices	threshold value reached: ≥350 N	
4. Acoustic performance	Rw ≥ 33 dB (-1; -5)	
5. Thermal Transmitance	Uw ≤ 1,3 W/(m².K)	
6. Radiation properties	Solar factor: g ≤ 0,65	
	Light transmittance: ≤ 0,82	
7. Air permability	3	