

## DECLARATION OF PERFORMANCE

No V/T/S70/B/01/07/2013

1. Unique identification code of the product-type **TREND STAR 70 - balcony doors - Veka Softline70**
2. Intended use/es: Single and multi-leaf windows and balcony doors with aluminum threshold, without resistance to fire and/or smoke leakage characteristics, intended to be used in domestic and commercial locations
3. Manufacturer: Filplast Sp. z o.o.  
ul. 3 Maja 33  
PL-48-250 Głogówek  
Poland
4. Authorised representative: -
5. System/s of AVCP: 3
- 6a. Harmonised standard: EN 14351-1:2006+A2:2016
- Notified body/ies: No 0757, IFT Rosenheim GmbH.

7. Declared performance/s:\*

Essential Characteristics	Performance	Harmonised standard
7.1. Watertightness	4A	EN 14351-1:2006+A2:2016
7.2. Dangerous substances	npd	
7.3. Resistance to wind load	B3	
7.4. Load-bearing capacity of safety devices	threshold value reached: $\geq 350$ N	
7.5. Acoustic performance	$R_w \geq 33$ dB (-1; -5)	
7.6. Thermal Transmittance	$U_w \leq 1,3$ W/(m <sup>2</sup> .K)	
7.7. Radiation properties	Solar factor: $g \leq 0,65$	
	Light transmittance: $\leq 0,82$	
7.8. Air permability	4	

The performance of the product(s) identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Jacek Sikorski  
Dyrektor ds. Technicznych  
Głogówek, dnia 20.07.2018



No V/T/S70/B/01/07/2013

Manufacturer:  
Filplast Sp z o.o., ul. 3 Maja 33,  
PL-48-250 Głogówek, Poland  
13



EN 14351-1:2006+A2:2016

Single and multi-leaf windows and balcony doors with aluminum threshold, without resistance to fire and/or smoke leakage characteristics, intended to be used in domestic and commercial locations

Notified body/ies: No 0757

**TREND STAR 70 - balcony doors - Veka Softline70**

Declared performance/s:

Essential Characteristics	Performance	Harmonised standard
1. Watertightness	4A	EN 14351-1:2006+A2:2016
2. Resistance to wind load	B3	
3. Load-bearing capacity of safety devices	threshold value reached: $\geq 350$ N	
4. Acoustic performance	$R_w \geq 33$ dB (-1; -5)	
5. Thermal Transmittance	$U_w \leq 1,3$ W/(m <sup>2</sup> .K)	
6. Radiation properties	Solar factor: $g \leq 0,65$	
	Light transmittance: $\leq 0,82$	
7. Air permeability	4	