

## DECLARATION OF PERFORMANCE

No V/S70/D/01/07/2018

1. Unique identification code of the product-type **TREND STAR 70 - pedestrian doorset - Veka Softline 70**
2. Intended use/es: External pedestrian doorset without resistance to fire and/or smoke leakage characteristics, intended to be used in domestic and commercial locations
3. Manufacturer: Filplast Sp. z o.o.  
ul. 3 Maja 33  
PL-48-250 Głogówek  
Poland
4. Authorised representative: -
5. System/s of AVCP: 3
- 6a. Harmonised standard: EN 14351-1:2006+A2:2016
- Notified body/ies: No 0757, IFT Rosenheim GmbH.

7. Declared performance/s:\*

Essential Characteristics	Performance	Harmonised standard
7.1. Watertightness	4A	EN 14351-1:2006+A2:2016
7.2. Dangerous substances	npd	
7.3. Resistance to wind load	C2	
7.4. Load-bearing capacity of safety devices	threshold value reached: $\geq 350$ N	
7.5. Thermal Transmittance	$U_d \leq 1,5$ W/(m <sup>2</sup> .K)	
7.6. Radiation properties	Solar factor: $g \leq 0,65$	
	Light transmittance: $\leq 0,82$	
7.7. Air permability	3	
7.8. Height and width	npd	

The performance of the product(s) identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by

Jacek Sikorski  
Dyrektor ds. Technicznych  
Głogówek, dnia 20.07.2018



No V/S70/D/01/07/2018

Manufacturer:  
Filplast Sp z o.o., ul. 3 Maja 33,  
PL-48-250 Głogówek, Poland  
13



EN 14351-1:2006+A2:2016

External pedestrian doorset without resistance to fire and/or smoke leakage characteristics, intended to be used in domestic and commercial locations  
Notified body/ies: No 0757

**TREND STAR 70 - pedestrian doorset - Veka Softline 70**

Declared performance/s:

Essential Characteristics	Performance	Harmonised standard
1. Watertightness	4A	EN 14351-1:2006+A2:2016
2. Resistance to wind load	C2	
3. Load-bearing capacity of safety devices	threshold value reached: $\geq 350$ N	
4. Thermal Transmittance	$U_d \leq 1,5$ W/(m <sup>2</sup> .K)	
5. Radiation properties	Solar factor: $g \leq 0,65$	
	Light transmittance: $\leq 0,82$	
6. Air permability	3	